

Package: gapmap (via r-universe)

October 12, 2026

Title Drawing Gapped Cluster Heatmaps with 'ggplot2'

Version 1.0.0

Description The gap encodes the distance between clusters and improves interpretation of cluster heatmaps. The gaps can be of the same distance based on a height threshold to cut the dendrogram. Another option is to vary the size of gaps based on the distance between clusters.

License GPL-2 | GPL-3

Encoding UTF-8

Depends ggplot2, reshape2

Imports grid

Suggests knitr, dendsort, RColorBrewer, rmarkdown

VignetteBuilder knitr

URL <https://github.com/evanbiederstedt/gapmap>

BugReports <https://github.com/evanbiederstedt/gapmap/issues>

RoxygenNote 7.2.3

NeedsCompilation no

Maintainer Evan Biederstedt <evan.biederstedt@gmail.com>

Config/pak/sysreqs libicu-dev

Repository <https://evanbiederstedt.r-universe.dev>

Date/Publication 2024-01-22 17:42:04 UTC

RemoteUrl <https://github.com/evanbiederstedt/gapmap>

RemoteRef HEAD

RemoteSha e5664e487abd0032b4b5533cacb4cc18317b4eff

Contents

gapmap-package	2
gap_data	3
gap_dendrogram	4
gap_heatmap	4
gap_label	5
gapmap	6
sample_tcga	8
Index	9

gapmap-package	<i>Draws gapped heatmap (gapmap) and gapped dendrograms using ggplot2 in [R].</i>
----------------	---

Description

Functions for drawing gapped cluster heatmap with ggplot2

Details

This is a set of tools for drawing gapmaps using [ggplot](#)

[gap_data](#) extracts data from a dendrogram object. Make sure to convert hclust object to dendrogram object by calling `as.dendrogram()`. This method generates an object class `gapdata`, consisting of a list of `data.frames`. The general workflow is as following:

1. Hierarchical clustering `hclust()`
2. Convert the `hclust` output class into dendrogram by calling `as.dendrogram()`
3. Generate a gapped cluster heatmap by specifying a matrix and dendrogram objects for rows and columns in `gapmap()` function

Author(s)

Ryo Sakai <ryo.sakai@esat.kuleuven.be>

gap_data*Generate a gapdata class object from a dendrogram object*

Description

This function takes a dendrogram class object as an input, and generate a gapdata class object as an output. By parsing the dendrogram object based on parameters for gaps, gaps between leaves in a dendrogram are introduced, and the coordinates of the leaves are adjusted. The gaps can be based on the a height (or distance) threshold to to introduce the gaps of the same width, or quantitative mapping of distance values mapped linearly or exponentially.

Usage

```
gap_data(  
  d,  
  mode = c("quantitative", "threshold"),  
  mapping = c("exponential", "linear"),  
  ratio = 0.2,  
  scale = 0.5,  
  threshold = 0,  
  verbose = FALSE,  
  ...  
)
```

Arguments

d	dendrogram class object
mode	gap mode, either "threshold" or "quantitative"
mapping	in case of quantitative mode, either "linear" or "exponential" mapping
ratio	the percentage of width allocated for the sum of gaps.
scale	the sclae log base for the exponential mapping
threshold	the height at which the dendrogram is cult to infer clusters
verbose	logical for whether in verbose mode or not
...	ignored

Value

a list of data frames that contain coordinates for drawing a gapped dendrogram

gap_dendrogram	<i>Function to draw a gapped dendrogram</i>
----------------	---

Description

This function draws a gapped dendrogram using the ggplot2 package. The input for the function is the gapdata class object, generated from gap_data() function.

Usage

```
gap_dendrogram(  
  data,  
  leaf_labels = TRUE,  
  rotate_label = FALSE,  
  orientation = c("top", "right", "bottom", "left"),  
  ...  
)
```

Arguments

data	gapdata class object
leaf_labels	a logical to show labels or not
rotate_label	a logical to rotate labels or not
orientation	a character to set the orientation of dendrogram. Choices are "top", "right", "bottom", "left".
...	ignored

Value

a ggplot object

gap_heatmap	<i>Function to draw a gapped heatmap</i>
-------------	--

Description

This function draws a gapped heatmap using the ggplot2 package. The input for the function are the gapdata class objects, generated from gap_data() function, and the data matrix.

Usage

```
gap_heatmap(
  m,
  row_gap = NULL,
  col_gap = NULL,
  row_labels = TRUE,
  col_labels = TRUE,
  rotate = FALSE,
  col = c("#053061", "#2166AC", "#4393C3", "#92C5DE", "#D1E5F0", "#F7F7F7", "#FDDBC7",
    "#F4A582", "#D6604D", "#B2182B", "#67001F")
)
```

Arguments

m	data matrix
row_gap	a gapdata class object for rows
col_gap	a gapdata class object for columns
row_labels	a logical to show labels for rows
col_labels	a logical to show labels for columns
rotate	a logical to rotate row labels
col	colors used for heatmap

Value

a ggplot object

gap_label	<i>Function to draw a gapped labels</i>
-----------	---

Description

This function draws a gapped labels using the ggplot2 package. The input for the function is the gapdata class object, generated from gap_data() function.

Usage

```
gap_label(data, orientation, label_size = 5)
```

Arguments

data	gapdata class object
orientation	orientation of the labels, "left", "top", "right", or "bottom"
label_size	a numeric to set the label text size

Value

a ggplot object

gapmap

*Function to draw a gapped cluster heatmap***Description**

This function draws a gapped cluster heatmap using the ggplot2 package. The input for the function is the a matrix, two dendrograms, and parameters for gaps.

Usage

```
gapmap(
  m,
  d_row,
  d_col,
  mode = c("quantitative", "threshold"),
  mapping = c("exponential", "linear"),
  ratio = 0.2,
  scale = 0.5,
  threshold = 0,
  row_threshold = NULL,
  col_threshold = NULL,
  rotate_label = TRUE,
  verbose = FALSE,
  left = "dendrogram",
  top = "dendrogram",
  right = "label",
  bottom = "label",
  col = c("#053061", "#2166AC", "#4393C3", "#92C5DE", "#D1E5F0", "#F7F7F7", "#FDDBC7",
    "#F4A582", "#D6604D", "#B2182B", "#67001F"),
  h_ratio = c(0.2, 0.7, 0.1),
  v_ratio = c(0.2, 0.7, 0.1),
  label_size = 5,
  show_legend = FALSE,
  ...
)
```

Arguments

m	matrix
d_row	a dendrogram class object for rows
d_col	a dendrogram class object for columns
mode	gap mode, either "threshold" or "quantitative"
mapping	in case of quantitative mode, either "linear" or "exponential" mapping
ratio	the percentage of width allocated for the sum of gaps.
scale	the sclae log base for the exponential mapping

threshold	the height at which the dendrogram is cut to infer clusters
row_threshold	the height at which the row dendrogram is cut
col_threshold	the height at which the column dendrogram is cut
rotate_label	a logical to rotate column labels or not
verbose	logical for whether in verbose mode or not
left	a character indicating "label" or "dendrogram" for composition
top	a character indicating "label" or "dendrogram" for composition
right	a character indicating "label" or "dendrogram" for composition
bottom	a character indicating "label" or "dendrogram" for composition
col	colors used for heatmap
h_ratio	a vector to set the horizontal ratio of the grid. It should add up to 1. top, center, bottom.
v_ratio	a vector to set the vertical ratio of the grid. It should add up to 1. left, center, right.
label_size	a numeric to set the label text size
show_legend	a logical to set whether to show a legend or not
...	ignored

Value

a ggplot object

Examples

```
set.seed(1234)
#generate sample data
x <- rnorm(10, mean=rep(1:5, each=2), sd=0.4)
y <- rnorm(10, mean=rep(c(1,2), each=5), sd=0.4)
dataFrame <- data.frame(x=x, y=y, row.names=c(1:10))
#calculate distance matrix. default is Euclidean distance
distxy <- dist(dataFrame)
#perform hierarchical clustering. default is complete linkage.
hc <- hclust(distxy)
dend <- as.dendrogram(hc)
#make a cluster heatmap plot
gapmap(m = as.matrix(distxy), d_row= rev(dend), d_col=dend)
```

`sample_tcga`*Sample data matrix from the integrated pathway analysis of gastric cancer from the Cancer Genome Atlas (TCGA) study.*

Description

a multivariate table obtained from the integrated pathway analysis of gastric cancer from the Cancer Genome Atlas (TCGA) study. In this data set, each column represents a pathway consisting of a set of genes and each row represents a cohort of samples based on specific clinical or genetic features. For each pair of a pathway and a feature, a continuous value of between 1 and -1 is assigned to score positive or negative association, respectively.

Usage

```
data(sample_tcga)
```

Format

A data frame with 215 rows and 117 variables

Details

We would like to thank Sheila Reynolds and Vesteinn Thorsson from the Institute for Systems Biology for sharing this sample data set.

Index

- * **datasets**

- sample_tcga, [8](#)

- * **package**

- gapmap-package, [2](#)

gap_data, [2](#), [3](#)

gap_dendrogram, [4](#)

gap_heatmap, [4](#)

gap_label, [5](#)

gapmap, [6](#)

gapmap-package, [2](#)

ggplot, [2](#)

sample_tcga, [8](#)